



Toyo Seiki Seisaku-sho, Ltd. 5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

No.632 Electric Wire Flammability Tester



■ APPLICATION

The **Cable Flammability Tester** conducts vertical flammability test of electric wires. It consists of draft chamber, combustion unit and calibration kit.

■ SPECIFICATIONS

Draft	Approx. 1800 x 1400 x 1600mm
Smoke exhaust	Built-in duct with damper
Burner	Conforms to ASTM D 5025, built-in <ul style="list-style-type: none"> ■ Inner diameter: $\varnothing 9.5 \pm 0.3$mm ■ Length: 100 ± 10mm ■ Inclination angle: 20°
Specimen	450 ± 10 mm
Power requirement	Single-phase, AC100V, 50Hz or 60Hz, 0.5kVA
Dimensions	W2200 x D1500 x H2600mm <i>Note: H2700mm is required for carry-in</i>
Weight	Approx. 300kg
Related standard	UL 1581 ASTM D5025, D5207

■ OPTIONS

Name	Model (Part No.)	Photo
Gloves	K-G	----
Combustion case <ul style="list-style-type: none"> ■ 3-way stainless steel plate ■ W300 x D350 x H600mm 	CA	----
Recorder <ul style="list-style-type: none"> ■ 1 pen (thermometer is not provided) 	K (Main unit together with recorder)	----

Specifications are subject to change without notice.



TOYO SEIKI SEISAKU-SHO, LTD.

5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

Tel:+81-3-3916-8183 Fax:+81-3-3916-8173

www.toyoseiki.co.jp

20200925 MN