

Toyo Seiki Seisaku-sho, Ltd. 5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

No.430 Rotary Abrasion Tester Model TS-2



Left: Rotary Abrasion Tester model TS-2 Right: Refacer model TSR-1 (Optional)

APPLICATION

The **Rotary Abrasion Tester** is used in a very wide field of applications as an abrasion tester of various kinds of flat materials. On rotating specimen, two abrasion wheels eccentric with regard to the center of the specimen are rotated pressing against the specimen, so that friction occurs at the contact of the specimen surface and abrasion wheels. Various kinds of abrasion wheels are available according to test specimen. Roughness of these wheels differs according to their number. Evaluation of degree of abrasion is made in terms of reduction in specimen's weight, thickness, gloss, etc.

■SPECIFICATION

Model	TS-2	
Rotation speed	60rpm or 72rpm	
Load	250, 500, 1000gf	
Counter	6-digits	
Standard abrading	1 set of CS-10 or CS-17	
wheels provided		
Power requirement	Single-phase, AC100V, 50Hz or 60Hz, 1kVA	
Dimensions	W275 x D410 x H500mm	
Weight	Approx. 18kg	
Related standards	JIS A 1453, K 5600, K 6264, K 7204	
	ISO 9352	

OPTIONS

Refacer model, TSR-1

Power requirement	Single-phase, AC100V, 50Hz or 60Hz, 0.5kVA	
Dimensions	W220 x D265 x H300mm	
Weight	Approx. 11kg	

Specimen holders (Turn tables)

E-100-125	Standard specimen holder	
E-14	Ring clamp specimen holder	
E-21	NEMA type specimen holder	

Abrading wheels

7 torading Wi			<u>, </u>	
Resilient	CS-10F	Light abrasion	Flexible plastics and coatings,	
(Elastic)		Load: 250g, 500g	Paper etc.	
Wheels	CS-10	Medium abrasion	Medium hard plastics and coatings,	
		Load: 500g, 1000g	Cardboard, Leather, Textiles etc.	
	CS-17	Coarse abrasion	Hard plastics and coatings, Ceramic,	
		Load: 500g, 1000g	Glass, Insulated wires etc.	
Non-resilient	H-10	Fine abrasion	Glass, Cardboard etc.	
(Non-elastic)		Load: 500g, 1000g		
Wheels	H-18	Medium abrasion	Glass, Rubber, Wood, Cardboard,	
		Load: 250g, 500g, 1000g	Textiles, Floor-coverings etc.	
	H-22	Very coarse abrasion	Wood, Leather, Shoe soles,	
		Load: 250g, 500g, 1000g	Cardboard, Rubber, Textiles,	
			Insulated wires etc.	
	H-38	Fine grain	Woven fabrics etc.	
		Load: 250g, 500g		
Others	S-11	Abrasive discs for refacing Resilient wheels		
	(For CS-10F, CS-10, CS-17)			
	S-32	Abrasive wheels		
	S-42	Sandpaper for S-32		

Specifications are subject to change without notice.



TOYO SEIKI SEISAKU-SHO, LTD.

5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan Tel:+81-3-3916-8183 Fax:+81-3-3916-8173 www.toyoseiki.co.jp

20200826 MN